




WARNING:

For dimensional, thermal or operating problems, IGLOO use in CLAY PAKY projectors other than those listed or other brand projectors is NOT permitted.

PROJECTOR	 MINIMUM ambient temperature	 MAXIMUM ambient temperature
<ul style="list-style-type: none"> • Alpha Spot 300 • Alpha Spot HPE 300 • Alpha Wash 300 • Alpha Beam 300 • Alpha Spot HPE 700 • Alpha Beam 700 • Alpha Profile 700 • Alpha Profile 700 ST • Alpha Wash 700 • Sharpy • Sharpy Wash 330 • A.leda Wash K5 • A.leda Wash K10 • A.leda Wash K20 • A.leda Wash K10 CC • A.leda Wash K10 TW • A.leda Wash K10 W • A.leda Wash K20 CC • A.leda Wash K20 TW • A.leda Wash K20 W • A.leda B-Eye K10 • A.leda B-Eye K10 Easy • A.leda B-Eye K10 CC • A.leda B-Eye K20 • A.leda B-Eye K20 CC 	<p>- 20 °C - 4 °F</p>	<p>+ 40 °C + 104 °F</p>
<ul style="list-style-type: none"> • SUPERSHARPY • MYTHOS 	<p>- 20 °C - 4 °F</p>	<p>+ 25 °C + 77 °F</p>

UNPACKING AND PREPARATION



IST008/001